

## TAGIC CB series specifications chart

Model type		0 Zero series					0 Zero-ECO series			
		CB-OF	CB-OF1	CB-OF2	CB-OH	CB-OH1	CBD-0JF	CBD-0JH	CBD-0HIA	
Cleaning method		Spray								
Processing method		Batch								
Guideline for cleaning time		5 minutes to 1 minutes								
Door opening and closing		Manual operation			Automatic		Manual operation	Automatic		
Frame import and export		Fixed								
Characteristics		Compact, space saving			Compact		Centrifugal dehydration		Ionized water	
Maximum dimensions of washed item	mm	Φ500×300	Φ650×360	Φ750×360	Φ500×300	Φ650×300	Φ400×100	Φ400×100	Φ500×300	
Maximum weight of washed item	kg	50	100	100	50	100	50	50	50	
Washing pressure	MPa	0.35	0.4	0.4	0.35	0.4	0.35	0.35	0.5	
Washing liquid flow rate	ℓ/min	80	100	100	80	100	80	80	80	
Tank capacity	ℓ	90	140	150	90	140	90	90	130	
Pump output	kW	1.1	1.5	1.5	1.1	1.5	1.1	1.1	1.5	
Heater output	kW	4.5	6	9	4.5	6	4.5	4.5	9	
Unit exterior dimensions	mm	W	680	820	955	680	820	700	700	680
	D	1215	1352	1451	1240	1380	1430	1460	1460	
	H	1100	1156	1156	1795	1830	1100	1770	1920	
Height when door is open	mm	1530	1695	1752	–	–	1610	–	–	
Dry weight	kg	150	190	200	180	200	200	230	250	