

TAGIC CB series specifications chart

Model type		Hinge door type series				Lift door type series					
		CB-2A	CB-3A	CB-4A	CB-5A	CB-1HPA	CB-2HPA	CB-3HPA	CB-4HPA	CB-5HPA	CB-7HPA
Cleaning method		Spray									
Processing method		Batch									
Guideline for cleaning time		5 minutes to 1 minute									
Door opening and closing		Manual operation				Automatic					
Frame import and export		Manual operation									
Characteristics		Washing of large/various items				Washing of large/various items (Labor saving)					
Maximum dimensions of washed item	mm	730×730×670	845×845×740	1100×1100×800	1280×1280×900	560×560×500	730×730×630	845×845×700	1100×1100×800	1280×1280×900	1540×1540×900
Maximum weight of washed item	kg	500	700	1200	1200	300	500	700	1200	1200	1200
Washing pressure	MPa	0.45	0.45	0.4	0.45	0.3	0.45	0.45	0.4	0.45	0.5
Washing liquid flow rate	ℓ /min	200	300	400	530	130	200	300	400	530	670
Tank capacity	ℓ	200	250	400	500	110	200	250	400	500	900
Pump output	kW	3	5.5	5.5	7.5	2.2	3	5.5	5.5	7.5	11
Heater output	kW	9	9	13.5	18	6	9	9	13.5	18	36
Unit exterior dimensions	W	1900	2090	2361	2760	1565	1900	2090	2395	2760	3510
	D	1290	1460	1820	1980	1120	1255	1425	1745	1935	2550
	H	1840	1900	2100	2110	1710	1840	1900	1900	2110	2255
Height when door is open	mm	2034	2269	2930	3148	2050	2290	2410	2445	2810	2950
Dry weight	kg	600	820	900	1140	350	600	820	850	1140	1650